

Alside (Vinyl) Doors

Measuring Your Doors

Step one: Count total door openings that you want replaced.

Step two: Determine your door layout.

Step three: Determine the type of door for each opening.

Step three: Measure the door's width and height in inches then add the measurements together to get the total united inches.

Step Four: Determine the glass options desired for each door.

Step five: Choose your grid options.

Step Six: Choose the frame color.

Opening One

Measurement Height + Width = Total United Inches

Material

Type

Color

Layout

Glass Option

Grid Option

Screen Option

Opening Two

Measurement Height + Width = Total United Inches

Material

Type

Color

Layout

Glass Option

Grid Option

Screen Option

Opening Three

Measurement Height + Width = Total United Inches

Material

Type

Color

Layout

Glass Option

Grid Option
Screen Option

Opening Four
Measurement Height + Width = Total United Inches
Material
Type
Color
Layout
Glass Option
Grid Option
Screen Option

Opening Five
Measurement Height + Width = Total United Inches
Material
Type
Color

Layout

You have the option to have a two, three or four panel door. This will also be determined by the size of your door opening.

Glass Options

CLIMATECH: Double glazed unit with PPG intercept spacer, one surface of PPG solar ban 60-lowE glass and argon gas.

CLIMATCH PLUS: Double glazed unit with foam spacers, one surface of PPG solar ban 60 lowE glass and argon gas.

CLIMATECH 2: (LOWE ON TWO SURFACES/ARGON): Double glazed unit with PPG intercept spacer, two surfaces of PPG solar ban 60 lowE glass and argon gas.

CLIMATECH TG2: Triple glazed unit with PPG intercept spacer, two surfaces of PPG Solar ban 60 LowE glass and two spaces filled with argon gas. **Special Note: this option is only available with Ultramaxx, Casement and Awning window lines.**

TINT: For additional window appearance you can choose from gray or bronze tint.

SUN CLEAN: (self cleaning glass) PPG sun clean is a self cleaning glass coated with photo catalytic and hydrophilic properties combined to result in a window that is easier to clean. Sun clean is available on all Climatech options except Climatech 2.

SECUREST: (Laminated Glass) Laminated glass using a 30 mil. plastic interlayer bonded between two layers of glass by heat and pressure.

TEMPERED GLASS: Heat hardened glass that if broken breaks in small pieces, limiting the chance of being severely cut.

GLASS BREAKAGE WARRANTY: not available for sliding glass doors.

Grid Option

Grid Colors: White, white wood grain, light oak wood grain, dark oak wood grain, cherry wood grain, american brown wood grain and brass.

Grid types:

Colonial grids: checkered grids that can be laid out evenly or you can have more on top than on bottom. Colonial contoured.

Diamond grids: diamond shaped grids that can be laid out evenly or you can have more on top than on bottom.

Single prairie grids: single line outlining the window both vertically and horizontally with both lines crossing each at the corners. This feature can span through both sashes or be broken into both sashes.

Double prairie grids: double line grid outlining the window both vertically and horizontally with both lines crossing each at the corners. This feature can span through both sashes or be broken into both sashes.

Exterior Painted Finishes

If you wish to have the exterior of the door frame to be a color other than white or beige you will need to choose an exterior laminate color. The color option is:

American Brown

Interior Frame Laminates

If you wish to have the interior of the door frame to be a color other than white or beige you will have to choose an interior laminate color. The color options are:

Light oak wood grain, dark oak wood grain, cherry wood grain, american brown wood grain

Screens

Fiberglass, Aluminum